


ANY SPOT

WIRELESS MICROPHONES



ANY SPOT 700 SERIES



GENERAL FEATURES

- 700 selectable channels
- Frequency Display
- Single and dual rack mount kit
- Carrying case
- RF and AF indicator
- Up to 35 simultaneous systems***
- Transmitters function from 2 AA batteries (can be rechargeable)
- DC Port on Receiver to charge a Transmitter
- DC Charger Cable (for use with rechargeable batteries)

	PART #		
700 SERIES WITH HH7 HANDHELD Includes: AS-M700R, AS-HH7 (with metal casing)	AS-M700/HH7		
700 SERIES HEADSET/LAV Includes AS-M700R, AS-MBP7, AS-HLC omni directional headset/lav mic	AS-M700/HLC		
700 SERIES W/ HEADSET MIC Includes AS-M700R, AS-MBP7, AS-HS uni directional headset microphone	AS-M700/HS		
700 SERIES W/ LAV/LAPEL Includes AS-M700R, AS-MBP7, AS-LV lav microphone	AS-M700/LV		
700 SERIES W/ GUITAR CABLE Includes AS-M700R, AS-MBP7, AS-GTR instrument cable	AS-M700/GTR		

ANY SPOT 500 SERIES



GENERAL FEATURES

- 64 selectable channels
- Adjustable squelch
- Single and dual rack mount kit
- Carrying case
- RF and AF indicator
- Up to 32 simultaneous systems***
- Transmitters function from 2 AA batteries (can be rechargeable)
- DC Port on Receiver to charge a Transmitter
- DC Charger Cable (for use w/ rechargeable batteries)

500 SERIES W/ HH5 HANDHELD Includes: AS-M500R, AS-HH5	AS-M500/HH5		
500 SERIES W/ HEADSET/LAV Includes AS-M500R, AS-MBP5, AS-HLC omni directional headset/lav microphone	AS-M500/HLC		
500 SERIES W/ HEADSET MIC Includes AS-M500R, AS-MBP5, AS-HS uni directional headset microphone	AS-M500/HS		
500 SERIES W/ LAV/LAPEL Includes AS-M500R, AS-MBP5, AS-LV lav microphone	AS-M500/LV		
500 SERIES W/ GUITAR CABLE Includes AS-M500R, AS-MBP5, AS-GTR instrument cable	AS-M500/GT		



AS-HLC



AS-HS



AS-LV



AS-GT

	AS-CASEMIC	ANY SPOT CASE FOR MICS Holds 1 rack mount receiver, body pack transmitter or handheld microphone, and accessories.
	AS-DCC	DC CHARGER DC charger will charge up to 5 AS-1000R's or other DC chargeable units from Galaxy including AS-MBP5, AS-MBP7, AS-HH5 & AS-HH7. 5 charging cables included.
	AS-LRE	LONG RACK EARS long rack ears will mount any single Any Spot rack unit into one rack space
	AS-SRE	SHORT RACK EARS short rack ears will mount and two Any Spot rack units into two rack space; connecting plate included.
	AS-HLC	HEADSET/LAV COMBO OMNI MIC Omni directional, Will work as a headset or lav, Mini XLR connector. Works with both AS-MBP5 & AS-MBP7
	AS-HS	UNI HEADSET MIC W/ MINI XLR omni directional headset (dual ear) can also be used as a lapel microphone, mini XLR plug, works with both AS-MBP5 & AS-MBP7
	AS-LV	UNI LAV/LAPEL MIC W/ MINI XLR uni directional lav/lapel microphone, mini XLR plug, works with both AS-MBP5 & AS-MBP7
	AS-GTR	GUITAR CABLE 1/4" TO MINI XLR guitar/instrument cable, mini XLR plug, works with both AS-MBP5 & AS-MBP7

System Specifications

AS-M500R Receiver

Carrier Frequency Range	UHF band 682–698 MHz
Oscillator	PLL synthesized
Modulation	FM
Frequency Stability	0.005%
S/N ratio	>94dB, at 48KHz deviation and 60dBV antenna input
Power Supply	12V DC
Image and Spurious Rejection	80 dB minimum
Receiving Sensitivity	8 dBµV.
Selectivity	>50dB
AF Response	50Hz to 15KHz (3dB)
T.H.D.	<1% (at 1KHz)
IF Frequency	1 st : 56MHz; 2 nd : 10.7MHz
Dynamic Range	>96dB
Tone Signal	32.768KHz
Audio Output	XLR and ¼-inch

Handheld (AS-HH5)/Bodypack Transmitter (AS-MBP5)

Carrier Frequency Range	UHF band 682–698MHz
RF Power Output	10mW
Oscillator	PLL synthesized
Frequency Stability	0.005%
Maximum Deviation	48KHz
Spurious Emission	>60dB below carrier frequency
T.H.D.	<1% (at 1KHz)
Microphone Cartridge	AS-HH5: uni-directional electret dynamic AS-LV: uni-directional electret condenser AS-HLC: omni-directional electret condenser AS-HS: uni-directional electret condenser
Operating voltage	DC1.5V x 2 AA size dry or rechargeable batteries
Current consumption	65mA 5mA

AS-M700R Receiver

Carrier Frequency Range	UHF band 630–660MHz
Oscillator	PLL synthesized
Modulation	FM
Frequency Stability	0.005%
S/N ratio	>94dB, at 48KHz deviation and 60dBV antenna input
Power Supply	12V DC
Image and Spurious Rejection	80 dB minimum
Receiving Sensitivity	6 dBµV.
Selectivity	>50dB
AF Response	50Hz to 15KHz (3dB)
T.H.D.	<1% (at 1KHz)
IF Frequency	1 st : 56MHz 2 nd : 10.7MHz
Dynamic Range	>96dB
Tone Signal	32.768MHz
Audio Output	XLR and ¼-inch

Handheld (AS-HH7)/Bodypack Transmitter (AS-MBP7)

Carrier Frequency Range	UHF band 630–660MHz
RF Power Output	10mW
Oscillator	PLL synthesized
Frequency Stability	0.005%
Maximum Deviation	48KHz
Spurious Emission	>60dB below carrier frequency
T.H.D.	<1% (at 1KHz)
Microphone Cartridge	AS-HH7: uni-directional electret condenser AS-LV: uni-directional electret condenser AS-HLC: omni-directional electret condenser AS-HS: uni-directional electret condenser
Operating voltage	DC1.5V x 2 AA size dry or rechargeable batteries
Current consumption	70mA 5mA