

# The UltraLITE



## Especificaciones técnicas

### UltraLITE Specifications

Standard	DECT 6.0 (Digital Enhanced Cordless Telecommunications)
Frequency	1920 - 1930MHz (USA)
Euro Frequency	1880 - 1900MHz (EURO)
Weight	4 oz
Channel Bandwidth	1.728 GHz
Modulation Type	GFSK
Transmission Speed	1.152 Mbps (Baud Rate)
Duplexing	Time Division Duplex (TDD)
Speech Encoding	ADPCM / 32bit/s
RF Accessing	Time Division Multiple Access (TDMA)
Range	400m in open space
Headset Power Supply	Rechargeable Lithium 3.7 V / 800 mAh 3.0 Wh
Charger Power Supply	AC / adapter: INPUT 110-40Vac OUTPUT 5.0V - 1 1000mA
Charge Time	3 hours
Operation Time	6 hours
Storage Temperature	-10 C to 60 C

### The HUB Specifications

Standard	DECT 6.0 (Digital Enhanced Cordless Telecommunications)
Frequency	1920 - 1930MHz (USA)
Euro Frequency	1880 - 1900MHz (EURO)
Weight	4 oz
Connector	2.5mm 3.5mm plug-in
Dimensions	5.5" w x 1.5" d x 3.75" h
Channel Bandwidth	1.728 GHz
Modulation Type	GFSK
Transmission Speed	1.152 Mbps (Baud Rate)
Duplexing	Time Division Duplex (TDD)
Speech Encoding	ADPCM / 32bit/s
RF Accessing	Time Division Multiple Access (TDMA)
Range	400m in open space
Headset Power Supply	Rechargeable Lithium 3.7 V / 800 mAh 3.0 Wh
Charger Power Supply	AC / adapter: INPUT 110-40Vac OUTPUT 5.0V - 1 1000mA
Charge Time	3 hours
Operation Time	4 hours
Storage Temperature	-10 C to 60 C

**AUDIO** TECNOLOGÍAS™

Distribuidor oficial de

